




INVERTER IGBT MIG



MIG 250-1



STANDARD



OPTION

- ✘ Compact and portable with light weight
- ✘ 20kgs Spool is capable
- ✘ Waveform control by added stability of the arc, even at small current
- ✘ Welding Capability from 0.6mm to 1.2mm welding wire diameter
- ✘ Digital Voltmeter and Ammeter for easy viewing
- ✘ Protections including over-heat, over-voltage, low-voltage and over-current
- ✘ Spool gun function is optional

Semi Industrial DC 1 3 Phase Phase

Processes

- MIG(GMAW)
- FLUX CORED(FCAW)

Optional Accessories

- Earth cable and clamp
- Mig Torch
- Regulator



MODEL	MIG 250-1
Power Supply Voltage(V)	1-220/230/240±15%
Frequency(HZ)	50/60
Rated Input Power(KW)	7.8
Rated Input Current(A)	50
Duty Cycle(40°C 10min)	60% 250A 100% 200A
No Load Voltage(V)	47
Current Range(A)	50-250
Welding Voltage Range(V)	13.5-26.5
Efficiency(%)	≥ 85
Net Weight(KG)/(LB)	19.5 KG/43 LB
Dimensions(MM)/(Inch)	610*240*430/24*9.4*16.9
Power Factor	0.72
Wire Diameter(MM)	Fe:0.6/0.8/0.9/1.0/1.2 Ss:0.8/0.9/1.0/1.2
Protection Class	IP23
Insulation Class	F
Cooling	AF

www.crepow.com

CE RoHS

CREPOW

Welding & Cutting Technology

Configuration Powerful Mig Style