

300A



300A-00.0994.02



300A-00.2179.02



150G-00.2264

SPECIFICATIONS

Description	Model	ERP	cable section (mm ²)	Max. Current (A)	Weight (g)
Earth Clamp	300A	00.0994.02	6-25	300	126
	300A	00.2179.02	6-25	300	693
	150G	00.2264	6-25	300	150



CPA-0161



CPA-0162



CPA-0146



CPA-0207



CPA-0208



CPA-0164



CPA-0165



CPA-0166

SPECIFICATIONS

Description	Model	Max. Current (A)	Max. Clamp Distance (mm)	Weight (g)
Earth Clamp	CPA-0161	300	45	275
	CPA-0162	300	45	267
	CPA-0146	300	40	371
	CPA-0207	300	41.53	460
	CPA-0208	300	41.53	460
	CPA-0164	300	28	376
	CPA-0165	300	28	369
	CPA-0166	300	35	380

500A



500A-00.0995.02



500A-00.2180.02



500A-00.2248

SPECIFICATIONS

Description	Model	ERP	cable section (mm ²)	Max. Current (A)	Weight (g)
Earth Clamp	500A	00.0995.02	10-50	500	281
	500A	00.2180.02	10-70	500	1060
	500A	00.2248	16-50	500	584



CPA-0117



CPA-0167



CPA-0168



CPA-1010



CPA-1011



CPA-0170



CPA-0171



CPA-0105



CPA-0113



CPA-0172



CPA-0173



CPA-0101



CPA-0175



CPA-0176



CPA-0107



CPA-0177



CPA-0103



CPA-0178



CPA-0197

SPECIFICATIONS

Description	Model	Max. Current (A)	Max. Clamp Distance (mm)	Weight (g)
Earth Clamp	CPA-0117	500	59	600
	CPA-0167	500	59	615
	CPA-0168	500	40	644
	CPA-1010	500	/	1042
	CPA-1011	500	45	424
	CPA-0170	500	45.25	417
	CPA-0171	500	58	650
	CPA-0105	500	58	706
	CPA-0113	500	58	715
	CPA-0172	500	35	750
	CPA-0173	500	40	552
	CPA-0101	500	66	2015
	CPA-0175	500	/	1103
	CPA-0176	500	/	889
	CPA-0107	500	37	664
	CPA-0177	500	37	661
	CPA-0103	500	37	619
	CPA-0178	500	37	629
CPA-0197	500	37	640	

600A



CPA-0109



CPA-0102

SPECIFICATIONS

Description	Model	Max. Current (A)	Max. Clamp Distance (mm)	Weight (g)
Earth Clamp	CPA-0109	600	40	837
	CPA-0102	600	36	780

800A



CPA-0179



CPA-0174



CPA-0209

SPECIFICATIONS

Description	Model	Max. Current (A)	Max. Clamp Distance (mm)	Weight (g)
Earth Clamp	CPA-0179	800	37.5	1055
	CPA-0174	800	37.99	2000
	CPA-0209	800	37	1054

1000A



CPA-0180



CPA-0181



CPA-0182



CPA-0183



CPA-0200



CPA-0210

SPECIFICATIONS

Description	Model	Max. Current (A)	Max. Clamp Distance (mm)	Weight (g)
Earth Clamp	CPA-0180	1000	70	657
	CPA-0181	1000	65	1247
	CPA-0182	1000	66	3000
	CPA-0183	1000	56	2250
	CPA-0200	1000	115	4105
	CPA-0210	1000	140	6317

1200A



CPA-0184

SPECIFICATIONS

Description	Model	Max. Current (A)	Max. Clamp Distance (mm)	Weight (g)
Earth Clamp	CPA-0184	1200	56	1428

1500A



1500A-00.2849.01

SPECIFICATIONS

Description	Model	ERP	cable section (mm ²)	Max. Current (A)	Weight (g)
Earth Clamp	1500A	00.2849.01	16-140	1500	4500



CPA-0186



CPA-0187



CPA-0188



CPA-0212



CPA-0213

SPECIFICATIONS

Description	Model	Max. Current (A)	Max. Clamp Distance (mm)	Weight (g)
Earth Clamp	CPA-0186	1500	115	2275
	CPA-0187	1500	140	8500
	CPA-0188	1500	115	6230
	CPA-0212	1500	135	5000
	CPA-0213	1500	140	8000

2000A



CPA-0199



CPA-0211

SPECIFICATIONS

Description	Model	Max. Current (A)	Max. Clamp Distance (mm)	Weight (g)
Earth Clamp	CPA-0199	2000	140	11000
	CPA-0211	2000	110	8622

2500A



CPA-0189



CPA-0190



CPA-0202

SPECIFICATIONS

Description	Model	Max. Current (A)	Max. Clamp Distance (mm)	Weight (g)
Earth Clamp	CPA-0189	2500	77	7300
	CPA-0190	2500	110	10300
	CPA-0202	2500	/	10600