



MIG 160



- ❑ Compact and portable with light weight
- ❑ 5kgs Spool is capable
- ❑ Waveform control by added stability of the arc, even at small current
- ❑ Digital Voltmeter and Ammeter for easy viewing
- ❑ Protections including over-heat, over-voltage, low-voltage and over-current
- ❑ Spool gun function is optional

Light Industrial DC **1** Phase

Processes

- MIG(GMAW)
- FLUX CORED(FCAW)

Optional Accessories

- Earth cable and clamp
- Mig Torch
- Regulator



MODEL	MIG 160
Power Supply Voltage(V)	1-220/230/240±10%
Frequency(HZ)	50/60
Rated Input Power(KW)	4.6
Rated Input Current(A)	32
Duty Cycle (40 °C 10min)	40% 160A
	60% 135A
	100%105A
No Load Voltage(V)	46
Welding Current Range(A)	40-160
Welding Voltage Range(V)	12- 22
Efficiency(%)	85
Power Factor	0.65
Wire Diameter(MM)	0.6/0.8/0.9(Fe/Ss/Flux-Cored)
Net Weight(KG)/(LB)	12 KG/26.5 LB
Dimensions(MM)/(Inch)	471*213*400/18.5*8.4*15.7
Insulation Class	H
Protection Class	IP23
Cooling	AF

Configuration Powerful Mig Style

www.crepow.com

CE RoHS

CREPOW
Welding & Cutting Technology