


INVERTER IGBT MMA CELLULOSE



ARC 400



Heavy Industrial **3 Phase**

Processes

- STICK(SMAW)
- Air carbon cutting and gouging

Optional Accessories

- Earth cable and clamp
- Welding cable and holder
- Air carbon gouging torch
- Lift Tig Torch



- ☑ Input voltage compensation keeps welding parameters constant even when input voltage change±15%.
- ☑ Lowest input voltage can be 300Volts and highest one can be 470Volts.
- ☑ Thermal overload protection automatically shuts down the power source to prevent high repair cost
- ☑ Large digital volt and ammeters for easy viewing
- ☑ Forced cooling fan
- ☑ Suitable for 6010 and 7018 Stick welding
- ☑ High output and 100% duty cycle at 40°C



MODEL	ARC 400
Power Supply Voltage(V)	3-380/415±15%
Frequency(HZ)	50/60
Rated Input Power(KW)	19
Rated Input Current(A)	28.6
Output Voltage(V)	36
Duty Cycle(40°C 10min)	100% 400A
No Load Voltage(V)	75
Current Range(A)	20-400
Dimensions(MM)/(Inch)	570*290*530/22*11*21
Net Weight(KG)/(LB)	34.5 KG/165 LB
Protection Class	IP23
Insulation Class	H
Cooling	AF
Electrode Diameter	Φ1.6-Φ5.0
Electrode Type	6013,7018 etc.
Power Factor	0.9

Configuration Powerful Mig style

www.crepow.com

CE RoHS

CREPOW
Welding & Cutting Technology